

ENGJL-KCRB / ENGJL-KCRB2 / ENG2S-SKYC Throttle & Choke Cable Installation Instructions

STEP 1
Remove cable housings from the carburetor.

STEP 2
Remove the carburetor top cover.

STEP 3
Remove the throttle slide and choke anchor - recommend upending the carburetor and using the heel of your hand to firmly smack the carburetor body to free.

STEP 4
Slide the cable housings over each cable, insert each cable through the carburetor top cover. Install the large spring over the throttle cable and the small spring over the choke cable.

STEP 5
Install the throttle cable by pulling the throttle slide towards the carburetor top cover and aligning the throttle cable into the throttle slide recess.

STEP 6
Attach the choke anchor to the choke cable by aligning the choke cable end in the center of the choke anchor then twist the choke cable vertically to secure.

STEP 7
Install the throttle slide and choke anchor into the carburetor. Note the long groove on the throttle slide will need to be aligned with the lower detent in the carburetor.

STEP 8
Align and secure the carburetor top cover as well as both cable housings.

STEP 9
Adjust the choke lever to the fully open position and insert the choke cable into the front of the choke lever housing.

STEP 10
Wrap choke cable around choke lever so it fits into the cable groove and feed cable through the hole in the choke lever arm.

STEP 11
Adjust the choke lever to the fully closed position, pull the choke cable taught, secure the choke cable with the included brass cable end.

STEP 12
Install and secure the clutch lever to your handlebars. Refer to the complete kit installation instructions to install the throttle cable to the twist grip throttle.

